

MSP231

HDMI To USB 3.0 Capture



Key Features

- Plug and play, driver free on Win 10
- Support 4K@30Hz input
- Microphone audio mix and audio output
- USB 3.0 Power supply and mini USB power backup
- LED indicator

Specification

Connectors	Input	HDMI	1×HDMI-A
	Output	HDMI	1×HDMI-A
		USB 3.0	1×USB-A
	Audio	Mic	1×3.5mm Jack
Line Out		1×3.5mm Jack	
Power		1×Mini USB	
Performance	Input Resolutions	HDMI	SMPTE 720p@50/60 1080i@50/60 1080p@23.98/24/25/29.97/30/50/59.94/60 2160p@24/25/30 VESA 640×480@60 800×600@60 1024×768@60 1280×1024@60 1920×1080@60 3840×2160@24/25/30 4096×2160@24
	Output Resolutions	HDMI (Loop) USB (output resolution is not configurable)	SMPTE 1080p@60 VESA 1920×1080@60
	Supported Standard	HDMI	1.4
		USB	3.0
Power	Input Voltage	DC 5V 2A	
Environment	Working Temperature	-0 ~50℃	
	Humidity	20 - 90%	
Physical	Weight	Net (Device)	0.08kg
	Dimensions	Net (Device)	113mm×61mm×13mm

Application



Order Codes

Product Code	Item
601-0231-00-0	MSP231

Tel: +86-592-5771197 | Fax: +86-592-5788216 | E-mail: sales@rgbink.com
Headquarter: S601 Weiye Building, Torch Hi-Tech Development Zone, Xiamen, Fujian, P.R.C.

Specifications are correct at time of printing and subject to change or alteration without notice.

RGBlink[®]

www.rgbink.com

